


Channel Flow[®] Air Filters



Media Support protects the media pack from changes caused by increases in differential pressure.

Media Pack Configuration — in either a rolled or stacked format — is inherently strong, eliminating the need for a centertube and wrapper used in traditional air filters.

Stronger Seal Support provides better sealing support and reduces the chance for leaks.

Non-Metal Filter Element allows easier, more environmentally friendly disposal and is fully incinerable.

Durable Frame provides improved engine protection by fully enclosing the filter, protecting the media from damage during handling and preventing air from being drawn in through the sides of the filter.

Better by design

Hastings Premium Filters' broad coverage includes Channel Flow air filters with innovative design features to protect your engine's air intake system. Hastings' Channel Flow air filters mean pure performance, system protection and hours of trouble-free system operation.

How Channel Flow Filters Work

More Surface Area

The key to the Channel Flow filters is the element. Channel Flow media is formed by layering alternating rows of flat sheets and corrugated media. When completed, the media resembles a honeycomb network of channels. Elements can be formed in either a round or racetrack design. Alternating channels are sealed with a bead of adhesive as the media pack is formed.


Air enters an open channel on the inlet side and flows through the media and exits through an adjacent open channel. Contaminants remain trapped within the channels and won't dislodge during servicing.

Capacity

Traditional air filters have an average capacity of about 1 unit of contaminant per unit volume, whereas the Channel Flow filter holds 2 units of contaminant per unit volume. This gives Channel Flow twice the capacity of traditional air filters.

Efficiency

Tests show Channel Flow filters have an average efficiency of 99.99%. This means for



1. DIRTY AIR enters the Channel Flow filter through alternately opened channels on the intake side.

2. AIR TRAVELS toward the engine, moving through the media where contaminants are trapped.

3. CLEAN AIR exits the filter through alternately opened channels on the opposite end.

every 10,000 units of contaminant introduced to the filter, only one makes its way through. This is comparable to the efficiency of Hastings Filters' traditional heavy-duty air filters.

In-Line Flow Path

Along with additional components in the engine compartment, increased air flow is needed for higher performance engines. Increased air flow

is also needed to meet tougher exhaust emission standards.

With a traditional air filter, air typically enters through the side of the filter housing. The air must then work its way around the filter element, pass through the media, then turn 90° to exit the filter. By eliminating the turns the air needs to make in a traditional air filter, in-line air filters reduce air flow restriction.

Hastings vs. Leading Competitor



4400 East Highway 30 ■ P.O. Box 6006
Kearney, NE 68848-6006
PH: 800-887-8836 ■ FAX: 800-210-6906
Internet: www.hastingsfilter.com

